



TIGER INDUSTRIES LIMITED
WWW.TIGERIND.COM



MATERIAL SAFETY DATA SHEET

June 2002

INDUSTRIAL GRADE SULPHUR

SECTION I

GENERAL INFORMATION

Tiger Industries.
6444 -42 St. SE
Calgary, AB T2C 2V1

Telephone: (403) 279-2616
Fax: (403) 236-9049

Trade Name (Common Name or Synonym) – **INDUSTRIAL GRADE SULPHUR**; ELEMENATAL SULPHUR
Formula: S Molecular Weight: 32.06

SECTION II

TRANSPORTATION REQUIREMENTS (Non Regulated as per following exemptions/provisions, and observations):

US and Canadian Shipments: non regulated as per T.D.G.A.R.'s exemption part 2.3 (a)(xxviii) and 49 CFR (Canadian Shipments and Packagings 171.12 (a) and CFR 49 (Special Provisions 172.102 pt 30.)

International Shipments:

AIR (IATA): Exempted under Special Provision A 105 **SEA (IMDG):** Exempted as per Sulphur Observations Part 1 & 2

TRANSPORTATION EMERGENCIES: call collect **CANUTEC 613-996-6666 (24 hours).**

WHMIS: non-controlled product in accordance with sub-paragraph 13(a)(i-iv) or paragraph 14 (a) of the Hazardous Products Act.

SECTION III

FIRST AID MEASURES

Skin: Wash with mild soap and water.
Eyes: Irrigate thoroughly with copious quantities of plain water.
Inadequate irrigation may increase the irritation. Do not use Boric Acid.

SECTION IV **HAZARDS INFORMATION**

Inhalation: Sulphur dust may irritate the mucous membranes of the respiratory passages.
Ingestion: Solid sulphur is virtually non-toxic. It can be taken internally in fairly large doses without injury.
Skin: In some individuals, sulphur dust has an irritant action, which may be aggravated by perspiration or moisture.
Eyes: Sulphur dust is capable of irritating the inner surfaces of the eyelids.

Permissible Concentration: **None established.**

Unusual Chronic Toxicity: **N/A**

Flash Point °C
Pure Liquid S,
188 °C, (370 °F)
gm per cu. metre

Auto Ignition °C
Dust clouds,
190 °C, (374 °F)

Flammable Limits in Air (% by VOL)
Minimum explosion concentration is
approximately 35

Impure Liquid S,
168 °C, (335 °F)

Undispersed dust,
220 °C, (428 °F)
gm/m³

(0.035 oz per cu. ft.). Maximum
explosive concentration lies
between 1000 and 2000
probably about 1400 gm/m³,
(1.4 oz per cu. ft.).

***Unusual Fire and Explosion Hazards:**

Dust suspended in air is readily ignited by flame, static electricity or friction spark. Every reasonable step must be taken to minimize dust formation. Dust tight casings should be equipped with explosion relief vents. Sparkless electrical equipment is recommended. Handling equipment must be grounded or bonded to avoid static electricity. Keep away from sources of flame or sparks. Detailed recommendations in Manufacturing Chemists Association SD-74 and National Safety Council 612 Bulletins covering "Sulphur" should be followed when handling Sulphur.

Explosive Limits: **LEL 35 gm/m³**
 UEL 1400 gm/m³

SECTION V

PRECAUTIONS/PROCEDURES

*** Fire Extinguishing Agents Recommended:**

1. A fine water spray or fog is recommended.
2. CO₂ or dry chemical.
3. Small fires may be smothered with sand or solid sulphur.

*** Fire Extinguishing Agents to Avoid:**

Hoses and extinguishers with pressure streams should be avoided where solid sulphur is dusty or where it may create a further hazard by raising more dust clouds.

*** Special Fire Fighting Precautions:**

Because burning sulphur evolves sulphur dioxide, breathing apparatus or gas masks approved for use in acid-gas atmosphere should be used. Fumes from unprotected sulphur fires shall be avoided, if possible, by approaching for the upwind side.

*** Ventilation:**

Local exhaust if dusty conditions prevail.

*** Normal Handling:**

Avoid breathing dust and keep clothing as free from dust as possible.

*** Storage:**

Solid becomes corrosive to metals when stored wet. Sulphur/bentonite fertilizer will physically break down when exposed to moisture or water.

*** Spill or Leak:**

Shovel into disposal containers or cover with tarp. For landfill disposal, mix with limestone 3 times the weight of sulphur.

*** Special: Precautions/Procedures/Label Instructions.**

Eye wash equipment near the work area.

SECTION VI

PERSONAL PROTECTIVE EQUIPMENT

*** Respiratory Protection:**

Dust-type respirators shall be provided for dusty conditions. Breathing apparatus must be available for emergency use in case of fire.

*** Eyes and Face:**

Dust-tight goggles with plastic or rubber frames may be helpful in dusty conditions.

*** Hands, Arms and Body:**

Workers whose skin may be sensitive to sulphur dust should button collars, roll sleeves down, and gather trousers at the ankle. Gloves may be helpful.

*** Other Clothing and Equipment:**

Hard hat and safety shoes. Fire-retardant fabric is recommended. Sulphur impregnated clothing should not be worn.

SECTION VII PHYSICAL DATA

Material is (at normal conditions):

Liquid Solid Gas

Appearance and Odour

Bright yellow in Colour. May have slight sulphur odour.

Boiling Point

444 °C (832 °F)

Specific Gravity

Solid, 2.07 gm/ml

Vapour Density

> 1

**Solubility in Water
(% by weight)**

Insoluble

pH

Neutral when dry

**Vapour Pressure
(mm Hg at 20 °C)**

Solid: Less than 0.0001 mm. Hg at 20° C (68 °F).

**Evaporation Rate
(Butyl Acetate =)
(Ether =)**

N/A

% Volatiles by Volume

N/A

Melting Point

119 °C (246 °F)

SECTION VIII REACTIVITY DATA

Stability

Unstable Stable

Conditions to Avoid

The main hazards are fire and dust explosions.

Hazardous Polymerization Conditions to Avoid.

May occur Will not occur.

SECTION IX HAZARDOUS INGREDIENTS (Mixtures Only)

*** Material or Components:**

Mixtures with chlorates, nitrates or other oxidizing agents may be explosive. Sulphur will react with alkalis or alkaline earths.

NOTICE:

The data and information presented herein are based upon tests, research and reports which are considered by us to be reliable and believed to be accurate. The data and information are presented without warranty, guarantee or liability on our part, and are presented to the customer for his own consideration, investigation and verification.